

LULA™ PIPE SYSTEMS




Steel pipe and fitting rolled to plastic pipe sizes with integral socket and rubber seal ring

- LULA™ pipe system is totally interchangeable with plastic pipes and fittings
- LULA-LOCK™ pipe system is the same socket system used in the plastic pipe systems, with an option of the retaining wire incorporated in front of the seal to 'lock' the two pipes together
- LULA/LULA-LOCK™ pipe systems can be laid above or below the ground - no special backfill required
- Ideal for rocky areas, river or bridge crossings - no damage through exposure to UV
- Less likely to be subjected to illegal connections
- Full range of fabricated LULA™ fittings available, including reduction adaptors between LULA and CABLE-LOCK™ male and female ends
- Pipe size range: 63mm to 200mm OD
- Maximum working pressure: up to 25 bar

STEEL PIPES IN SIZE RANGE 63MM - 200MM OD

Pipe nominal size OD	Wall Thickness	Weight/6m length
63mm	2.0mm	15.8kg
75mm	2.0mm	18.9kg
90mm	2.0mm	28.4kg
110mm	2.0mm	35.1kg
160mm	2.8mm	71.5kg
200mm	3.0mm	96.1kg

FULL RANGE OF FABRICATED STEEL FITTINGS AVAILABLE



PVC pipe fits into LULA™ steel pipe
various lengths available

